

HFT

TRIFASE 400 Vac



APPLICAZIONI PRINCIPALI



BATTERIE ADATTE

Piombo acido - PzS

GEL - AGM - VRLA - PzV

Litio (su richiesta)

MODELLI DISPONIBILI

V	A	VAC	CODICE	Pb acido (Ah)		Gel (Ah)	Iac
				7-8h	10-11-14h	12-14h	Assorbimento
24	80	3x400	HFT 24/80	440-508	609-677-816	543-677	4,10
24	100	3x400	HFT 24/100	549-635	762-846-1020	679-846	5,10
24	120	3x400	HFT 24/120	659-762	914-1015-1224	814-1015	6,10
48	80	3x400	HFT 48/80	440-508	609-677-816	543-677	8,00
48	100	3x400	HFT 48/100	549-635	762-846-1020	679-846	10,00
48	120	3x400	HFT 48/120	659-762	914-1015-1224	814-1015	12,00
80	60	3x400	HFT 80/60	330-381	457-508-612	407-508	9,80
80	80	3x400	HFT 80/80	440-508	609-677-816	543-677	13,10
80	100	3x400	HFT80/100	549-635	762-846-1020	679-846	15,50

Versioni speciali 36V, 72V, 96V e 120V disponibili su richiesta

Versioni con correnti d'uscita intermedie disponibili

Air mix Ah= +10%

